MODEL: NV-210 [Needle Valve]

Connection: Screw BSPT, NPT



VTV VALVE, serving Multi-National end users in a wide range of applications in many industries

including: 1. Palm Oil and Refinery Plant

- 2. Petrochemical
- 3. Food Industries
- 4. General Industries



- 2. Oil
- 3. Gases
- 4. Non-abrasive media




♦ SPECIFICATIONS

- End Connections: NPT threaded, ASME B1.20.1
- DIN 2999 & BS21; ISO 228/1 & ISO 7/1
- Operating Temperature Range: -60 to 450°F
- Fire Safe design

◆ MATERIAL LIST

NO	PART NAME	MATERIAL SS304		
1	SET SCREW			
2	HANDLE	SS304		
3	STEM	SS316		
4	GLAND NUT	SS304		
5	GLAND NUT	SS304		
6	PACKING	TEFLON		
7	BONNET	SS316		
8	BODY	SS316		



◆ DIMENSIONS (mm)

SIZE	1/8"	1/4"	3/8"	1/2"	3/4"	1"
A	75	75	75	87	90	103
В	25	25	25	30	32.5	40
С	50	50	50	60	65	80
Cv	0.43	0.43	0.74	1.36	2.64	3.6

Maximun Operating Pressure - Temperature Data 1/8" to 1" Needlel Valve Model: VN01

